

BK0156-135






Height-Adjustable & Foldable LED All-in-One Display

Product Features

1. Adopts flip-chip and COB packaging technology.
2. Surface applies EBL technology to enhance ink color consistency.
3. Equipped with a height-adjustable and foldable stand design for convenient transportation and daily use.
4. Runs on Android 13 system, with 8GB running memory and 64GB storage space.



Product Views and Dimensions Display



Product Technical Specification Table

Category	Parameter	Details
Basic Parameters	Size	135 inches
	Aspect Ratio	16:09
	Screen Resolution	1920*1080
	Pixel Pitch	1.56 mm
	Area	5.06 m ²
	Dimensions	3010240836 mm
	Thickness	37 mm (Floor Stand) / 76 mm (Wall-Mounted)
	Flatness	≤0.1 mm
	Weight	≤120 KG
	Material	Die-Cast Aluminum
	Frame Material/Color	Aluminum Profile / Black
	Maintenance Method	Front Maintenance
	Installation Method	Floor-Mounted, Wall-Mounted
Display Parameters	Package Type	COB
	Service Life	≥120000 H
	Horizontal/Vertical Viewing Angle	H: 170° / V: 170°
	Brightness	600 nits
	Refresh Rate	3840 Hz
	Frame Rate	50/60 Hz
	Gray Scale	14 bit
	Contrast Ratio	10000:1
	Color Temperature	2000K-15000K
	Pixel-Level Brightness Calibration	Supported
	Pixel-Level Chromaticity Calibration	Supported
	Brightness Uniformity	≥99%
	Color Uniformity	Within ±0.001 Cx, Cy
Motherboard Parameters	Operating System	Android 13.0
	CPU	4A73 + 4A53
	RAM/ROM	8GB DDR4 / 64GB
	Interfaces	HDMI out1 / USB3.02 / Audio out1 / LAN1 / SPDIF1 / USB2.03 / HDMI in*3
	WIFI	WiFi 5 + WiFi 6
	Bluetooth	5.1
	Remote Control	Supported

Product Technical Specification Table

Category	Parameter	Details
OPS (Optional)	CPU	I5 7400 (4 Cores)
	RAM	8G
	ROM	256G
	Network	1xRTL8111H 10/100/1000M (RJ45 LAN)
	Operating System	Windows 10
Touch Parameters (Optional)	Touch Technology	Infrared
	Touch Points	10 Points
	Touch Accuracy	±1 mm
	Response Time	9ms
	Two-Point Touch Spacing	25 mm
	Touch Input Method	Opaque Objects
	Minimum Touch Size	6mm (Single-Point Touch), 8mm (Multi-Point Touch)
Audio Parameters	Installation Mode	Built-in
	Rated Power	15W*2
Operating Parameters	Input Voltage	AC 100V ~ 240V, 50-60Hz
	Standby Power Consumption	≤0.5 W
	Average Power Consumption	600 W
	Peak Power Consumption	1750 W
	Operating Temperature/Humidity	-10℃ ~ +45℃ / 10~80% RH
	Storage Temperature/Humidity	-20℃ ~ +50℃ / 10~70% RH
Standard Accessories	Installation Stand	1 set
	600*337.5 Cabinet	25 pcs
	Frame	1 set
	Bottom Control Box	1 set
	Power Supply & Signal Cables	1 set
	Cabinet Connecting Plates & Screws	1 set
	Remote Control	1 pcs
	Spare Module	2 pcs
	Manual Vacuum Chuck	1 pcs
Optional Accessories	Wireless Projector	1 pcs
	Infrared Touch Frame	1 set
	OPS Module	1 pcs
	Camera	1 pcs